

Wyse 60 Personalities

ASCII: Wyse WY-60, WY-50/WY-50+, ADDS Viewpoint A2/60, Televideo, TVI-910+/920/925/950/955, Hazeltine 1500, Lear Siegler ADM 3A/5/31, IBM 3101 1X/2X, IBM 3161

ANSI: WY-75 mode, DEC VT-100/52, Data General D200/210, PC Terminal, Wyse 60

Display Features

Colors: Paper-white (P-188), amber (P-134), or green (P-31) phosphors

Monitor: 14-inch diagonal, flat screen, non-glare CRT

Refresh: 60 Hz refresh

Adjustments: Tilt -7 to +34 degrees and 360 degree swivel

Character cell: 10x16 (80 columns); 9x16 (132 columns)

Format: 26/44 lines by 80/132 columns, up to seven pages

Option: Height-adjustable arm

Wyse 60 Keyboards:

Detached keyboard with 4-wire coiled cable

6-feet extended length

Two-position tilt

DIN compliant

Full touch keys

Approximately 350 nonvolatile bytes available

64 non-volatile bytes maximum per key

Layout:

Enhanced PC (102 keys)

Int'l Enhanced PC (103 keys)

Wyse ASCII (101 keys)

Wyse ANSI (101 keys)

Languages:

US English, Danish, French, German, Norwegian, Spanish, Swedish, Swiss, UK English

Options: Localization kits

- **Wyse 60 Communications**
- Modes: Full/half duplex, block, and monitor (debug)
- Modem and Aux.: EIA RS-232 serial, DB-25 connector; up to 38.4 Kbaud
- Printer: RS-232 serial, DB-25 connector, up to 19.2 Kbaud
- **Shipping Weight:**
- Terminal and Keyboard: 20lbs (9.8 kg)
- **Wyse 60 Power**
- 120 VAC+/- 10%, 47-63 Hz
- 240 VAC+/- 10%, 47-63 Hz
- **Regulatory Compliance of Wyse 60 Terminals**
- Safety: UL 478 and CSA 220 approved; TÜV-GS approved (selected models)
- RF Interference: FCC Class A Complies with EPA Energy Star guidelines
- **Wyse 60 Key Features**
- Best selling general purpose terminal
- ASCII/ANSI/PCTerm terminal
- Choice of keyboards ASCII/ANSI/Enhanced PC keyboard
- High resolution character mode with 44/132 display format
- Ergonomic Design with optional height-adjustable arm